

7450 / 7759 Mentor Remote Keypad / Microphone Units



In certain applications it is not possible to locate the complete Zone 1 Mentor Station in the vicinity of the user. Such requirements are:

- a) Use of operator controls in a Zone 1 IIC atmosphere
- b) Restricted space

For either situation it is possible to locate the host Mentor station in a Zone 1 II A/B atmosphere remotely from the associated microphone & keypad "man / machine" interface. A number of Remote keypad / microphone assembly options are available. Note that on certain variants it is also possible to incorporate a remote headset socket too.

Mentor Model Identification

Model	300mm Goose Neck Microphone	600mm Goose Neck Microphone	Flush Fit Microphone	Headset Socket	Flush Fit Mount	Surface Mount	Mentor Orbital	Mentor Digital
Ex 7450	✗	✗	✓	✗	✓	✗	7404	✗
Ex 7451	✓	✗	✗	✗	✓	✗	7404	✗
Ex 7452	✗	✓	✗	✗	✓	✗	7404	✗
EE 7752	✓	✗	✗	✗	✓	✗	✗	7711/10
EE 7753	✗	✓	✗	✗	✓	✗	✗	7711/10
EE 7754	✓	✗	✗	✓	✓	✗	✗	7711/15
EE 7755	✗	✓	✗	✓	✓	✗	✗	7711/15
EE 7756	✓	✗	✗	✗	✗	✓	✗	7711/10
EE 7757	✗	✓	✗	✗	✗	✓	✗	7711/10
EE 7758	✓	✗	✗	✓	✗	✓	✗	7711/15
EE 7759	✗	✓	✗	✓	✗	✓	✗	7711/15

Spector Lumenex have a policy of continuous product improvement therefore this information is subject to change without notice.

© Copyright. This publication is the property of Spector Lumenex & may not be copied or transmitted without the express written permission of Spector Lumenex.